



Since 1966, Ferlegno has produced advanced wall partition systems, finishes and custom furniture. Collaborating with the best design studios, from the initial concept design and space planning phases through to the completion of the implementation phase.

In the best tradition of Made in Italy, which always prioritizes high-quality production, creativity in design and form, product durability, the company offers a service based on innovative architectural and technical solutions, custom-made, where attention to detail and environmental protection go hand in hand.

The design and production of partition walls is the core business of the company, which is part of the Coiver Group. The Research and Development division develops, engineers, and supervises the production of all the cataloged partition wall lines, depending on the different needs of the designers and the customization requests of the customers.

Ferlegno, both in Italy and abroad, directly installs all the cataloged products, ensuring certified quality and providing all the necessary after-sales services.




# ESSENTIAL CHARACTER

The ICE partition wall offers the possibility of integrating and housing electrical components during the design phase. The profiles are able to compensate for any unevenness in both the floor and ceiling and the glass sheets can be customized both in size and finish (available in extra clear, transparent, etched, lacquered and smoked variants).

Any infill panels can be made with glass or wooden sheets. The ICE system can also be integrated with tempered glass swing doors. The door swing profile, also made of extruded aluminium, is provided with an appropriate cavity for the insertion of a technical sealing gasket.

The switch is contained in the frame profile, without the need for an additional technical module. The design is completed by a door closer and invisible recessed hinges.





### Choose your features. handle.

## Technical

#### WALL DETAILS WITH OR WITHOUT FRAME

2, 3 or 4 ways.

#### **ADJUSTMENTS**

Horizontal ± 20 mm Vertical ± 15 mm

#### **DOORS**

Thick framed single-glazed swing door 50 mm with invisible hinges and acoustic guillotine.

Hinged door in monolithic polished edge glass 10 mm with visible hinges.

Door in standard or acoustic honeycomb thickness 40 mm with invisible hinges and, optionally, acoustic guillotine.

Possibility of accessorizing the doors with an anti-panic handle.

Sliding door with single-glass door with polished edge or framed with track with the same height as the wall

Acoustic performances: 38 dB (6+6), 35 dB (5+5).

#### **ACCESSORIES AND OTHER TECHNICAL ELEMENTS**

Possibility of installing single-place Vimar or Bticino switches or sockets on the door upright without the need to create a technical shaft.

#### DIMENSION

Wall thickness 37 mm. Frame thickness 50 mm. Glass thickness of 12 mm (6+6) or 10 mm (5+5). Framed door glass thickness 5+5.1 mm. Monolithic door glass thickness 10 mm.

#### **PROFILES**

Anodized and polished









RAL painted



Any sample color.

#### **BLIND PANELS**

Wood









Extra clear

















Via Bizzozzero 93–95 20032 Cormano Milan, Italy

+39 0266301899 preventiviferlegno@coiver.it



